

# ZTrak™ PRO 900 Series

Z925A | Z930A | Z950A | Z960A | Z970A



Accept nothing less.



# Introducing the New ZTrak PRO.

It's about decks stamped out of the thickest steel. It's about increased power and better control. And it's about running all day, with ease.

No matter what you're looking for in a commercial zero-turn mower, you'll find it in the new Z900 lineup. We have the widest breadth of horsepower choices in the industry: all the way to 37. Our c-channel frames have been rebalanced for superior weight distribution. New transmissions for more efficient use of power. And improved reliability in the deck drive system.

Visit your local John Deere dealer and see for yourself the difference a ZTrak PRO will make in your business.

## Z900 Specifications



Z925A

### Engine

Manufacturer	Kawasaki
Horsepower (gross)	27 hp (20.1 kw)
Displacement	52 cu. in. (852 cc)
Crankshaft Orientation	Vertical
Crankcase Capacity	2.0 U.S. quart (1.89 L)
Cooling	Air
Air Cleaner	Heavy-duty canister type w/ safety
Fuel Type	Gas
Fuel Tank Capacity	11.5 U.S. gallons (43.5 L)
Hour Meter	Standard, digital
Operator Presence Starting System	Brake and Go (standard)

### Diagnostics

Type	On-board
------	----------

### Drive Train

Hydraulic Drive	Kanzaki heavy-duty ground drive
Hydraulic Capacity	2.8 U.S. quarts (2.65 L) (per side)
Filter	Internal, replaceable
Travel Speed Forward	0 - 12 mph (0-19.3 km/h)
Travel Speed Reverse	0-5 mph (0-8.1 km/h)
Drive Tires	24x12-12
Front Caster Wheels	No Flat, Semi-pneumatic rounded shoulder 13x6.5-6

### Brakes

Park Brake	Internal wet disk
Park Brake Actuation	Foot pedal

### PTO

Type	Electro-magnetic (250 lb. ft.)
PTO Activation/Deactivation	Pull knob

### Mower Deck

Available Side Discharge Widths	60 in. (152.4 cm)
Available Mulch On Demand Widths	54 in. MOD (137.2 cm)
Deck construction	One-piece stamped steel
Deck thickness	7 ga. (0.177 in.)
Height-of-Cut Range	1.5-5.0 in. (3.8-12.7 cm)
Increments	0.25 in. (0.6 cm)
Blade Tip Speed	18,000 f/m

### Anti-Scalp Wheels

Front Anti-Scalp Wheels	Double captured right, center, and left
Rear Anti-Scalp Wheels	Double captured right, center and left

### Dimensions

Length	84 in. (213.4 cm)
Width (deck chute down)	68 in., 74 in. (172.7, 188 cm)
Height with ROPS up	73 in. (185.4 cm)
Height with ROPS Down	47 in. (119.4 cm)
Ground Clearance	5 in. (12.7 cm)
Weight	1408 lbs. (w/60" deck)

<b>Warranty</b>	<b>2 year commercial - unlimited hours</b>
-----------------	--

\* Comfort & Convenience package

C&C= Comfort & Convenience package



**Z930A**



**Z950A**



**Z960A**



**Z970A**

Kawasaki	Kawasaki	Kawasaki	Kawasaki
29 hp (21.6 kw)	31 hp (23.1 kw)	34 hp (25.4 kw)	37 hp (27.6 kw)
52 cu. in. (852 cc)	52 cu. in. (852 cc)	61 cu. in. (999 cc)	61 cu. in. (999 cc)
Vertical	Vertical	Vertical	Vertical
2.0 U.S. quart (1.89 L)	2.0 U.S. quart (1.89 L)	2.0 U.S. quart (1.89 L)	2.0 U.S. quart (1.89 L)
Air	Air	Air	Air
Heavy-duty canister type w/ safety	Heavy duty canister type w/ safety	Heavy duty canister type w/ safety	Heavy duty canister type w/ safety
Gas	Gas	Gas	Gas
11.5 U.S. gallons (43.5 L)	11.5 U.S. gallons (43.5 L)	11.5 U.S. gallons (43.5 L)	11.5 U.S. gallons (43.5 L)
Standard, digital	Standard, digital	Standard, digital	Standard, digital
Brake and Go (standard)	Brake and Go (standard)	Brake and Go (standard)	Brake and Go (standard)

On-board	On-board	On-board	On-board
----------	----------	----------	----------

Kawasaki heavy-duty ground drive	Kawasaki heavy-duty ground drive	Kawasaki heavy-duty ground drive	Kawasaki heavy-duty ground drive
2.8 U.S. quarts (2.65 L) (per side)	2.8 U.S. quarts (2.65 L) (per side)	2.8 U.S. quarts (2.65 L) (per side)	2.8 U.S. quarts (2.65 L) (per side)
Internal, replaceable	Internal, replaceable	Internal, replaceable	Internal, replaceable
0 - 12 mph (0-19.3 km/h)	0 - 12 mph (0-19.3 km/h)	0 - 12 mph (0-19.3 km/h)	0 - 12 mph (0-19.3 km/h)
0-5 mph (0-8.1 km/h)	0-5 mph (0-8.1 km/h)	0-5 mph (0-8.1 km/h)	0-5 mph (0-8.1 km/h)
24x12-12	24x12-12	24x12-12	24x12-12
No Flat, Semi-pneumatic rounded shoulder, 13x6.5-6	No Flat, Semi-pneumatic rounded shoulder, 13x6.5-6	No Flat, Semi-pneumatic rounded shoulder, 13x6.5-6	No Flat, Semi-pneumatic rounded shoulder, 13x6.5-6

Internal wet disk	Internal wet disk	Internal wet disk	Internal wet disk
Foot pedal	Foot pedal	Foot pedal	Foot pedal

Electro-magnetic (250 lb. ft.)	Electro-magnetic (250 lb. ft.)	Electro-magnetic (250 lb. ft.)	Electro-magnetic (250 lb. ft.)
Pull knob	Pull knob	Pull knob	Pull knob

60 in. w/C&C, 72 in. (152.4 & 182.9 cm)	60 in., 72 in. w/C&C (152.4 & 182.9 cm)	60 in. w/C&C., 72 in. w/C&C (152.4 & 182.9 cm)	72 in. w/C&C (182.9 cm)
60 in. MOD (152.4 cm)	60 in. MOD (152.4 cm)	60 in. MOD w/C&C * (152.4 cm)	_____
One-piece stamped steel	One piece stamped steel	One piece stamped steel	One piece stamped steel
7 ga. (0.177 in.)	7 ga. (0.177 in.)	7 ga. (0.177 in.)	7 ga. (0.177 in.)
1.5-5.0 in. (3.8-12.7 cm)	1.5-5.0 in. (3.8-12.7 cm)	1.5-5.0 in. (3.8-12.7 cm)	1.5-5.0 in. (3.8-12.7 cm)
0.25 in. (0.6 cm)	0.25 in. (0.6 cm)	0.25 in. (0.6 cm)	0.25 in. (0.6 cm)
18,000 f/m	18,000 f/m	18,000 f/m	18,000 f/m

Double captured right, center, and left	Double captured right, center, and left	Double captured right, center, and left	Double captured right, center, and left
Double captured right, center and left	Double captured right, center and left	Double captured right, center and left	Double captured right, center and left

84 in. (213.4 cm)	84 in. (213.4 cm)	84 in. (213.4 cm)	84 in. (213.4 cm)
74 in., 86 in. (188, 218.4 cm)	74 in., 86 in. (188, 218.4 cm)	74 in., 86 in. (188, 218.4 cm)	86 in. (218.4 cm)
73 in. (185.4 cm)	73 in. (185.4 cm)	73 in. (185.4 cm)	73 in. (185.4 cm)
47 in. (119.4 cm)	47 in. (119.4 cm)	47 in. (119.4 cm)	47 in. (119.4 cm)
5 in. (12.7 cm)	5 in. (12.7 cm)	5 in. (12.7 cm)	5 in. (12.7 cm)
1408 lbs. w/60" deck)	1408 lbs. w/60" deck)	1449 lbs. (w/60" MOD deck)	1501 lbs. (w/72" deck)
2 year commercial - unlimited hours	2 year commercial - unlimited hours	2 year commercial - unlimited hours	2 year commercial - unlimited hours

MOD=Mulch-on-Demand

## We perform where it matters most.



7-Iron PRO Mulch on Demand Mower deck

### Mowing performance

Nothing in the industry matches our stamped, seven-gauge steel 7-Iron Pro deck, nor our exclusive Mulch-on-Demand deck. We also have the speed you're after: 12 mph. Even on our smaller engines, we have larger displacement for more power.



7-Iron PRO Mower deck



Comfort and Convenience package

### Controllability

Our Z900s feature a brand new integrated ground drive transmission with a piston motor, gear reduction drive, and internal wet disk brakes for improved efficiency and longer life. And our exclusive Comfort & Convenience package has ergonomically angled control levers with thick padded grips. Even better, the levers contain built-in electronic controls that let you raise or lower the deck as well as disengage the mower blades.



Exclusive Brake and Go system

### Ease of Use

From the very start, the Z900 is an operator's dream, thanks to our exclusive Brake and Go system. To start the machine, all you need is for the foot-actuated parking brake to be engaged. Easy is everywhere: a dial-in height of cut adjustment is located right on the control arm. On-board self-diagnostics. And run-flat tires that keep you going no matter what.



Redesigned frame and new transmission

