

# Z920A

## ZTrak™ PRO 900 Series

### Specifications



[JohnDeere.com/MowPro](http://JohnDeere.com/MowPro)

Specifications are based on published information at the time of publication. Specifications are subject to change without notice. Contact your local John Deere dealer for more information. Prices are subject to change without notice. In all cases, current published price lists and incentive program bulletins will take precedence. This literature has been compiled for worldwide circulation. While general information, pictures and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specification, design and price of the products described in this literature without notice. John Deere's green and yellow color scheme, the leaping deer symbol, and JOHN DEERE are trademarks of Deere & Company. \*The engine horsepower and torque information are provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower and torque will be less.

<b>Engine</b>	
Manufacturer	Kawasaki
Horsepower (gross)	26 hp (19.4 kw)
Displacement	44.5 cu. in. (730 cc)
Cylinders	Two
Crankshaft Orientation	Vertical
Crankcase Capacity	2.0 U.S. quart (1.89 L)
Oil Filter	Full flow, replaceable
Lubrication	Full pressure
Cooling	Air
Air Cleaner	Heavy duty canister type w/safety element
Pre-Cleaner	Yes
Muffler	Single walled steel
<b>Fuel System</b>	
Fuel Tank Location	Left side
Fuel Type and Capacity	Gas
Fuel Pump	11.5 U.S. gallons (43.5 L)
Fuel Gauge	Pulse type
Fuel Delivery System	Yes
Fuel Tank Switch/Shut Off Valve	Self priming / Yes
<b>Electrical System</b>	
Ignition	Solenoid shift
Charge System	20 amp
Battery Voltage and CCA	12 volt / 300
Hour Meter	Standard, digital
Operator Presence Starting System	Standard, Brake & Go™
<b>Diagnostics</b>	
	On-board
<b>Drive Train</b>	
Hydraulic Pumps	Tuff Torq
Hydraulic Capacity	2.8 U.S. quarts (2.65 L) (per side)
Filter	Internal, replaceable
<b>Travel Speed</b>	
Forward	0-10.5 mph (0-16.9 km/h)
Reverse	0-5 mph (0-8.1 km/h)
Speed and Direction Control	Twin levers
<b>Tires</b>	
Drive Tires	24x9.5-12 Turf (48 in. MOD Deck) 24x12-12 Turf (54 in. & 60 in. Deck)
Drive Tire Pressure	10-12 psi
Front Caster Wheels	No Flat, Semi-pneumatic rounded shoulder, 13x6.5-6
<b>Brakes</b>	
Dynamic Braking	Twin levers
Park Brake and Actuation	Internal wet disk / Foot pedal
<b>PTO</b>	
Type	Electro-Magnetic (200, 250 ft.-lbs.)
Drive	V-belt
PTO Activation and Deactivation	Pull knob / Pull knob
<b>Mower Decks</b>	
Available Widths	48 in., 54 in., 60 in (121.9 cm), (137.2 cm) & (152.4 cm)
MOD Widths	48in. MOD (121.9 cm)
Deck construction	One piece stamped steel
Deck thickness	7 gauge (0.177 in.)
Height-of-Cut Range	1.5-5.0 in. (3.8-12.7 cm)
Increments	0.25 in. (0.6 cm)
<b>Blades</b>	
Tip Speed	18,000 f/m
<b>Anti-Scalp Wheels</b>	
Front Anti-Scalp Wheels	Double captured right, center, and left
Rear Anti-Scalp Wheels	Double captured right, center and left
<b>Dimensions</b>	
Length	84 in. (213.4 cm)
Width (deck chute down)	62 in., 68 in., 74 in (157.5, 172.7, 188 cm)
Height with ROPS up / down	73 in. (185.4 cm) / 47 in. (119.4 cm)
Ground Clearance	5 in. (12.7 cm)
Weight	1320 lbs. (w/48" deck)
<b>Warranty</b>	
	2 year single source - unlimited hours

